



The pump is a submersible drainage pump fitted with cast iron open impeller and stainless steel strainer. The pump can handle particles up to 10mm.

The pump is characterised by:

- Cast iron pump body and impeller for durability
- Fully automatic operation.
- Dual silicon carbide/ceramic & carbon/ceramic mechanical seals with oil lip seal
- Carry handle.
- Versatile outlet connection.
- 240V single phase motor with in-built auto reset thermal overload.
- 10m of power cable.
- Dewatering of cellars, garages etc.
- Pumping clean or slightly dirty water
- Flows to 300L/min
- Heads to 10 m

Electrical data:

| | |
|---------------------|---------------------------|
| Rated voltage: | 240V |
| Mains frequency: | 50 Hz |
| Rated output: | 400W |
| Current: | 3.5 amps |
| Capacitor: | 20 uF |
| Motor duty: | Continuous |
| Motor type: | Asynchronous |
| Motor protection: | In-built thermal overload |
| Ingress protection: | IP 68 |
| Insulation class: | F |
| Power cable length: | 10 m H07RNF |
| Net weight: | 11 kg |
| Dimensions: | 143Lx224Hx350W (mm) |

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

| | |
|-------------|----------------------------------------------------------------------------------|
| Pump body: | Cast Iron |
| Strainer: | 304 SS |
| Impeller: | Cast iron |
| Shaft: | Stainless Steel 410 |
| Shaft seal: | Dual silicon carbide/ceramic & carbon/ceramic mechanical seals with oil lip seal |

Installation:

| | |
|------------------------------|-------|
| Maximum ambient temperature: | 40 °C |
| Pipe connections discharge: | 2" F |

2 Year Bianco Pumpz Warranty

