



The pump is a submersible drainage pump fitted with cast iron semi vortex impeller.

The pump can handle particles up to 17mm.

The pump is characterised by:

- Cast iron pump body and impeller for durability
- Fully automatic operation.
- Dual silicon carbide/ceramic & carbon/ceramic mechanical seals with oil lip seal
- Carry handle.
- Versatile outlet connection.
- 240V single phase motor with in-built auto reset thermal overload.
- 10m of power cable.
- Dewatering of cellars, garages etc.
- Pumping clean or slightly dirty water
- Flows to 430L/min
- Heads to 11 m

Electrical data:

Rated voltage:	240V
Mains frequency:	50 Hz
Rated output:	750W
Current:	5.5 amps
Capacitor:	20 uF
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	In-built thermal overload
Ingress protection:	IP 68
Insulation class:	F
Power cable length:	10 m H07RNF
Net weight:	37 kg
Dimensions:	155Lx260Hx435W (mm)

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

Pump body:	Cast Iron
Impeller:	Cast iron
Shaft:	Stainless Steel 410
Shaft seal:	Dual silicon carbide/ceramic & carbon/ceramic mechanical seals with oil lip seal

Installation:

Maximum ambient temperature:	40 °C
Pipe connections discharge:	3" F

2 Year Bianco Pumpz Warranty

