

BIANCO PUMPZ

DS: 01-10-06
Subject: BIANCO...
GARDEN PUMP
MODEL: BIA-TECH40
Distribution: ALL

PRODUCT PROFILE

BIA-TECH40



The pump is a self-priming garden pump supplied wired and ready to install.

The self-priming ability provides excellent suction capacity and is easy to reprime if you run out of water.

Used especially for transferring water in domestic installations.

The pump is characterised by:

- Corrosion resistant pump body, diffuser and impeller.
- Mechanical shaft seal.
- 240V single phase TEFC motor with in-built auto reset thermal overload.
- 10 m power lead and on/off switch.

Liquid:

Clean water temperature range:

2 – 35 deg C

Materials:

Pump body, Diffuser, Impeller:

Technopolymer

Mechanical seal:

Carbon/Ceramic/Nitrile

O rings:

Nitrile

Installation:

Maximum ambient temperature:

40 deg C

Maximum operating pressure

6 bar

Pipe connections suction/discharge:

1" BSP F / 1" BSP M

Electrical data:

Rated voltage: 240V

Mains frequency: 50 Hz

Rated output: 400W

Current: 1.7 amps

Capacitor: 10 uF

Motor duty: Continuous

Motor type: Asynchronous, TEFC

Motor protection: In-built thermal overload, On/off switch

Ingress protection: IP 54

Insulation class: F

Power cable length: 10 m x HO7 RNF

Net weight: 7.0 kg

Dimensions: 340mm L x 405mm H x 230mm W

Pump Performance.

Flows to 25 l/m

Heads to 27m



Distributed by **White International Pty Ltd** A.B.N. 48 000 119 380
52 – 60 Ashford Avenue NSW 2214 PO Box 4755 Milperra BC 1891
Ph (02) 9783 6000 Fax (02) 9783 6001
SALES HOTLINE 1300 783 601 SALES FAXLINE 02 9783 6003